LAN Extension and Network Virtualization in Cloud Data Centers



Raj Jain
Washington University in Saint Louis
Saint Louis, MO 63130
Jain@cse.wustl.edu

These slides and audio/video recordings of this class lecture are at:
http://www.cse.wustl.edu/~jain/cse5700-25/

Student Questions

©2025 Raj Jain



Overview

1. TRILL
2. NVGRE
3. VXLAN
4. NVO3
5. Geneve
6. EVPN

Student Questions

©2025 Raj Jain

Geographic Clusters of Data Centers

- Multiple data centers are used to improve availability
- Cold-Standby: Data is backed up on tapes and stored off-site.
  In case of disaster, applications and data are loaded on standby.
  Manual switchover ⇒ Significant downtime. (1970-1990)
- Hot-Standby: Two servers in geographically close data centers exchange state and data continuously.
  Synchronous or Asynchronous data replication to standby.
  On a failure, the application automatically switches to standby.
  Automatic switchover ⇒ Reduced downtime (1990-2005)
  Only 50% of resources are used under normal operation.
- Active-Active: All resources are used. Virtual machines and data can be quickly moved between sites when needed.


Student Questions

Ref: G. Santana, "Datacenter Virtualization Fundamentals," Cisco Press, 2014, ISBN: 1587143240

©2025 Raj Jain

Data Center Interconnection (DCI)

- Allows distant data centers to be connected in one L2 domain
  - Distributed applications
  - Disaster recovery
  - Maintenance/Migration
  - High-Availability
  - Consolidation
- Active and standby can share the same virtual IP for switchover.
- Multicast can be used to send states to multiple destinations.




Student Questions

©2025 Raj Jain

Challenges of LAN Extension

- **Broadcast storms**: Broadcast, Unknown, and Multicast (BUM) may create an excessive floo
- **Loops**: Easy to form loops in a large network.
- **STP Issues**:
  - High spanning tree diameter (leaf-to-leaf): More than 7.
  - The root can become a bottleneck and a single point of failure
  - Multiple paths remain unused
- **Tromboning**: Dual attached servers and switches generate excessive cross-traffic
- **Security**: Data on LAN extension must be encrypted





Student Questions

©2025 Raj Jain

TRILL

- Transparent Interconnection of Lots of Links
- Allows a large campus to be a single extended LAN
- LANs allow free mobility inside the LAN but:
  - Inefficient paths using Spanning tree
  - Inefficient link utilization since many links are disabled
  - Inefficient link utilization since multipath is not allowed.
  - Unstable: small changes in network ⇒ large changes in spanning tree
- IP subnets are not good for mobility because IP addresses change as nodes move and break transport connections, but:
  - IP routing is efficient, optimal, and stable
- Solution: Take the best of both worlds
  ⇒ Use MAC addresses and IP routing

Student Questions


Ref: RFCs 5556, 6325, 6326, 6327, 6361, 6439

©2025 Raj Jain

TRILL Architecture

- Routing Bridges (RBridges) encapsulate L2 frames and route them to destination Rbridges, which decapsulate and forward
- Header contains a hop limit to avoid looping
- RBridges run IS-IS to compute pair-wise optimal paths for unicast and distribution trees for multicast
- RBridge learn MAC addresses by source learning and by exchanging their MAC tables with other RBridges
- Each VLAN on the link has one (and only one) designated RBridge using IS-IS election protocol

H= Host
RB=RBridge




Ref: R. Perlman, "RBridges: Transparent Routing," Infocom 2004

Student Questions

©2025 Raj Jain

TRILL Encapsulation Format



- For outer headers, both PPP and Ethernet headers are allowed. PPP for the long haul.
- Outer Ethernet header can have a VLAN ID corresponding to the VLAN used for TRILL.
- Priority bits in outer headers are copied from inner VLAN


Student Questions

©2025 Raj Jain

TRILL Features

- Transparent: No change to capabilities.
  Broadcast, Unknown, Multicast (**BUM**) support. Auto-learning.
- Zero Configuration: RBridges discover their connectivity and learn MAC addresses automatically
- Hosts can be multi-homed
- VLANs are supported
- Optimized route
- No loops
- Legacy bridges with spanning trees in the same extended LAN

Student Questions




TRILL: Summary

- TRILL allows a large campus to be a single Extended LAN
- Packets are encapsulated and routed using IS-IS routing

Student Questions

GRE

- Any new feature in IP requires *encapsulation*, a.k.a. *tunneling*
- Generic Routing Encapsulation (RFC 1701/1702)
- Generic ⇒ X over Y for any X or Y protocols
- Given *n* protocols, we need O(n^2) encapsulation formats, GRE converts this to O(1) format.
- Encapsulations may require the following services:
  - Stream multiplexing: Which recipient at the other end?
  - Source Routing: what path to take?
  - Packet Sequencing




Student Questions

©2025 Raj Jain

GRE (Cont)

- GRE provides all of the above encapsulation services
- Over IPv4, GRE packets use a protocol type of 47
- Optional: Checksum, Loose/strict Source Routing, Key
- Key is used either to authenticate the source or to distinguish different substreams
- Recursion Control: # of additional encapsulations allowed.
  0 ⇒ Restricted to a single provider network ⇒ end-to-end
- Offset: Points to the next source route field to be used
- IP or IPSec are commonly used as delivery headers





Student Questions

©2025 Raj Jain

EoMPLSoGRE

- Ethernet over MPLS over GRE (point-to-point)
  VPLS over MPLS over GRE (Multipoint-to-multipoint)
- Used when a provider offers only L3 connectivity
  Subscribers use their own MPLS over GRE tunnels
- VPLSoGRE or Advanced-VPLSoGRE can also be used
- GRE offers an IPSec encryption option






Student Questions

©2025 Raj Jain

End of Part 1

NVGRE

- Ethernet over GRE over IP (point-to-point)
- A unique 24-bit Virtual Subnet Identifier (VSID) is used as the lower 24 bits of the GRE key field ⇒ 2^{24} tenants can share
- A unique IP multicast address is used for BUM (Broadcast, Unknown, Multicast) traffic on each VSID
- Equal Cost Multipath (ECMP) allowed on point-to-point tunnels




Ref: P. Garg, Y. Wang, et al. "NVGRE: Network Virtualization Using Generic Routing Encapsulation Encapsulation", RFC 7637, IETF, September 2015.

©2025 Raj Jain

Student Questions

NVGRE (Cont)

- In a cloud, a pSwitch or a vSwitch can serve as a tunnel endpoint
- VMs need to be in the same VSID to communicate
- VMs in different VSIDs can have the same MAC address
- Inner IEEE 802.1Q tag, if present, is removed.



Ref: Emulex, "NVGRE Overlay Networks: Enabling Network Scalability," Aug 2012, 11pp., http://www.emulex.com/artifacts/074d492d-9dfa-42bd-9583-69ca9e264bd3/elx_wp_all_nvgre.pdf

©2025 Raj Jain

Student Questions

NVO3

- Network Virtualization Overlays using L3 techniques
- **Problem**: Data Center Virtual Private Network (DCVPN) in a multi-tenant datacenter
- Issues:
  - Scale in Number of Networks: Hundreds of thousands of DCVPNs in a single administrative domain
  - Scale in Number of Nodes: Millions of VMs
  - VM (or pM) Migration
  - Support both L2 and L3 VPNs
  - Dynamic provisioning
  - Addressing independence: Each tenant should be able to select its address space
  - Virtual Private ⇒ Other tenants do not see your frames
  - Optimal Forwarding: VMs should not be tied to a single designated router that may be far away.


Ref: T. Narten, Ed., "Problem Statement: Overlays for Network Virtualization," IETF RFC 7364, Oct 14, 23 pp.

Student Questions

©2025 Raj Jain

NVO3 Terminology

- **Tenant System (TS)**: VM or pM
- **Virtual Network (VN)**: L2 or L3 Tenant networks
- **Network Virtualization Edges (NVEs)**: Entities connecting TSs (virtual/physical switches/routers)
- NVEs could be in vSwitches, external pSwitches, or span both.
- **Network Virtualization Authority (NVA)**: Manages forwarding info for a set of NVEs
- NVA could be distributed or centralized and replicated.




Student Questions

©2025 Raj Jain

NVO3 Terminology (Cont)

- **Virtual Network (VN):** Provides L2/L3 services to a set of tenants
- **VN Context ID**: A field in the header that identifies a VN instance (VNI).
- **Overlay header** = inner header = Virtual Network Header
- **Underlay header** = outer header = Physical Network Header
- **Tenant Separation**: A tenant's traffic cannot be seen by another tenant



Student Questions

Current NVO Technologies

- BGP/MPLS IP VPNs: Widely deployed in enterprise networks. Difficult in data centers because hosts/hypervisors do not implement BGP.
- BGP/MPLS Ethernet VPNs: Deployed in carrier networks. Difficult in data centers.
- **802.1Q**, PB, PBB VLANs
- **Shortest Path Bridging**: IEEE 802.1aq
- Virtual Station Interface (VSI) Discovery and Configuration Protocol (VDP): IEEE 802.1Qbg
- Address Resolution for Massive numbers of hosts in the Data Center (ARMD): RFC6820
- **TRILL**
- **L2VPN**: Provider provisioned L2 VPN
- Proxy Mobile IP: Does not support multi-tenancy
- LISP: RFC 6830

Student Questions

©2025 Raj Jain

VXLAN

- Virtual eXtensible Local Area Networks (VXLAN)
- L3 solution to isolate multiple tenants in a data center (L2 solution is Q-in-Q and MAC-in-MAC)
- Developed by VMware. Supported by many companies in the IETF NVO3 working group
- Problem:
  - 4096 VLANs are not sufficient in a multi-tenant data center
  - Tenants need to control their MAC, VLAN, and IP address assignments ⇒ Overlapping MAC, VLAN, and IP addresses
  - Spanning tree is inefficient with a large number of switches ⇒ Too many links are disabled
  - Better throughput with IP equal cost multipath (ECMP)


Student Questions

Ref: M. Mahalingam, D. G. Dutt, et al. "VXLAN: A Framework for Overlaying Virtualized Layer 2 Networks over Layer 3 Networks," IETF RFC 7348, August 2014.

©2025 Raj Jain

VXLAN Architecture

- Create a virtual L2 overlay (called VXLAN) over L3 networks
- 2^{24} Virtual Network Instances (VNIs)
- Only VMs in the same VXLAN can communicate
- vSwitches serve as VTEP (VXLAN Tunnel End Point).
  $\Rightarrow$ Encapsulate L2 frames in UDP over IP and send to the destination VTEP(s).
- Segments may have overlapping MAC addresses and VLANs, but L2 traffic never crosses a VNI




Student Questions

©2025 Raj Jain

VXLAN Deployment Example


Example: Three tenants. 3 VNIs. 4 Tunnels for unicast.
+ 3 tunnels for multicast (not shown)



Student Questions

VXLAN Encapsulation Format

- Outer VLAN tag is optional.
  Used to isolate VXLAN traffic on the LAN
- Source VM ARPs to find the Destination VM's MAC address.
  All L2 multicasts/unknowns are sent via IP multicast.
  Destination VM sends a standard Ethernet ARP response.
- Destination VTEP learns Inner-Src-MAC-to-Outer-Src-IP mapping ⇒ Avoids unknown destination flooding for returning responses



Only key fields are shown

Student Questions


©2025 Raj Jain

VXLAN Encapsulation Format (Cont)

- Internet Group Multicast Protocol (IGMP) is used to prune multicast trees
- 7 of 8 bits in the flag field are reserved.
  One flag bit is set if the VNI field is valid
- UDP source port is a hash of the inner MAC header
  ⇒ Allows load balancing using Equal Cost Multi-Path using L3-L4 header hashing
- VMs are unaware that they are operating on VLAN or VXLAN
- VTEPs need to learn the MAC address of other VTEPs and client VMs of VNIs they are handling.
- A VXLAN gateway switch can forward traffic to/from non-VXLAN networks. Encapsulates or decapsulates the packets.

Student Questions

©2025 Raj Jain



VXLAN: Summary

- VXLAN solves the problem of multiple tenants with overlapping MAC addresses, VLANs, and IP addresses in a cloud environment.
- A server may have VMs belonging to different tenants
- No changes to VMs. Hypervisors are responsible for all details.
- Uses UDP over IP encapsulation to isolate tenants

Student Questions

End of Part 2

Geneve


- Generic Network Virtualization Encapsulation
- Best of NVGRE, VXLAN, and STT
- **Generic** ⇒ Can virtualize any (L2/L3/…) protocol over IP
- **Tunnel Endpoints**: Process Geneve headers and control packets
- **Transit Device**: do not need to process Geneve headers or control packets

Ref: J. Gross, et al, "Geneve: Generic Network Virtualization Encapsulation" IETF RFC 8926, 34 pp., November 2020.

Student Questions

Geneve Frame Format

- **Highly Extensible**: Variable number of variable size options
- Any vendor can extend it in its way by getting an "Option Class" from IANA (Internet Assigned Number Authority)
- Options are encoded in a **TLV** (Type-Length-Value) format



Student Questions

©2025 Raj Jain

Geneve Frame Format (Cont)


- **Option Length** (6 bits): Length of options field in 4B (does not include the rest of the Geneve header)
- **OAM Frame** (1 bit): Control packet. Does not contain user data. Must be passed on to the control plane CPU
- **Critical Options Present** (1 bit): One or more options are critical.
  Drop the packet if you don't understand a critical option
- **Payload Protocol Type** (16 bits): 0x6558 for Ethernet
- **Virtual Network ID** (24 bits): Tenant ID
- **Option Class** (16 bits): Who designed this option? Vendor, technologies, organizations, …
- **Option Type** (8 bits) : msb (most significant bit) =1 => Critical
- **Option Value Length** (5 bits): in units of 4 bytes

Student Questions

©2025 Raj Jain

LSO and LRO

- **Large Send Offload** (LSO): The host hands a large chunk of data to NIC and metadata. NIC makes MSS size segments and adds checksum, TCP, IP, and MAC headers to each segment.
- **Large Receive Offload** (LRO): NICs attempt to reassemble multiple TCP segments and pass larger chunks to the host. The host does the final reassembly with fewer per-packet operations.



Student Questions

©2025 Raj Jain

Geneve Implementation Issues

- **Fragmentation**: Use Path MTU (Maximum Transmission Unit) discovery to avoid fragmentation on the path
- **DSCP** (Differentiated Services Control Point): DSCP bits in the outer header may or may not be the same as in the inner header. Decided by the policy of the network service provider
- **ECN** (Explicit Congestion Notification): ECN bits should be copied from the inner header on entry to the tunnel and copied back to the inner header on exit from the tunnel
- **Broadcast and Multicast**: Use underlying networks' multicast capabilities if available. Use multiple point-to-point tunnels if multicast is not available.

Student Questions

Geneve Implementation Issues (Cont)

- **LSO**: Replicate all Geneve headers and options on all outgoing packets.
- **LRO**: Merge all packets with the identical Geneve headers
- **Option Order**: Not significant. Options can be in any order.
- **Inner VLAN**: Tunnel endpoints decide whether to differentiate packets with different inner VLAN values.

Student Questions

©2025 Raj Jain

Geneve Summary


1. UDP over IP encapsulation
2. Geneve header is extensible by vendors
3. Generally, variable length headers are considered hard for hardware implementation
4. Vendor extensibility requires a system to register options and may result in interoperability issues
5. This is subject to change since it is in the draft stage.

Student Questions

©2025 Raj Jain

Virtual Private LAN Service (VPLS)

- Allows *multi-point* Ethernet services over MPLS networks using a *full-mesh point-to-point pseudo-wires*
- **Virtual Forwarding Instance (VFI)**: A virtual LER instance in the provider edge router specific to each customer LAN
- **VPLS Instance**: Set of VFIs and PWs connecting them. Creates a single "VLAN" broadcast domain connecting VFIs.
- **BGP MPLS-Based Ethernet VPN (EVPN):** Widely deployed. Being extended to meet data center requirements



CE: Customer Edge
PE: Provider Edge


Ref: G. Santana, "Datacenter Virtualization Fundamentals," Cisco Press, 2014, ISBN: 1587143240
K. Kompella and Y. Rekhter, "Virtual Private LAN Service (VPLS) Using BGP for Auto-Discovery and Signaling," IETF RFC 4761, Jan 2007, https://tools.ietf.org/pdf/rfc4761

©2025 Raj Jain

Student Questions

EVPN Features

- Multicast Optimization: MP2MP LSPs
- Ease of Provisioning:
  - Auto-discovery of PEs,
  - Customer Site ID,
  - Automated designated Forwarder election among PEs,
  - MPLS parameters based on VLAN parameters
- New Service Interface:
  - Port = VLAN,
  - Multiple VLANs per port,
  - VLAN bundles are treated as one VLAN
- Fast Convergence after failures
- Flood Suppression for unknown unicast frames
- Flexible VPN topologies and Policies, e.g. E-Tree




Student Questions

©2025 Raj Jain

EVPN Redundancy Features

- Flow-based load balancing: CE connected to multiple PEs. Select path by hashing 7-tuple (L2, L3, L4 addresses, VLAN)
- Flow-based multi-pathing: Multiple LSPs between PEs
- Geo-Redundant PE Nodes: CE connected to multiple PEs in different PoPs
- Optimal Traffic Forwarding: Single/multi-homed CE to Single/multi-homed CE. Packet not forwarded to PEs not connected to the destination CE
- Flexible Redundancy Grouping: PEs are grouped for redundancy.
- Multi-homed Network: Entire Ethernet is connected to multiple PEs.




Ref: A Sajassi, et al., "BGP MPLS-Based Ethernet VPN," IETF RFC 7432, Feb 2015, https://tools.ietf.org/html/rfc7432
A. Sajassi, et al., "Requirements for Ethernet VPN (EVPN)," May 2014, https://tools.ietf.org/html/rfc7209

Student Questions

©2025 Raj Jain

Summary



1. TRILL uses "Routing Bridges" to transport Ethernet packets on a campus network. RBs use IS-IS to find the shortest path.
2. NVO3 is a generalized framework for network virtualization and partitioning for multiple tenants over L3. It covers both L2 and L3 connectivity.
3. NVGRE uses Ethernet over GRE for L2 connectivity.
4. VXLAN uses Ethernet over UDP over IP
5. Geneve uses Any protocol over UDP over IP encapsulation.

Student Questions

References

- G. Santana, "Datacenter Virtualization Fundamentals," Cisco Press, 2014, ISBN: 1587143240 (Safari Book)
- J. Gross, et al, "Geneve: Generic Network Virtualization Encapsulation," RFC 8926, 34 pp., November 2020, https://www.rfc-editor.org/rfc/rfc8926.pdf
- M. Lasserre, et al., "Framework for Data Center (DC) Network Virtualization," IETF RFC 7365, Oct 2014, 26 pp., https://tools.ietf.org/pdf/rfc7365
- M. Mahalingam, et al, "*VXLAN: A Framework for Overlaying Virtualized Layer 2 Networks over Layer 3 Networks*," IETF RFC 7348, https://tools.ietf.org/pdf/rfc7348
- P. Garg, Y. Wang, "NVGRE: Network Virtualization using GRE," Sep 2015, IETF RFC 7637, https://tools.ietf.org/pdf/rfc7637
- R. Perlman, "RBridges: Transparent Routing," Infocom 2004
- TRILL RFCs 5556, 6325, 6326, 6327, 6361, 6439
- T. Narten, Ed., "Problem Statement: Overlays for Network Virtualization," IETF RFC 7364, Oct 14, 23 pp., https://tools.ietf.org/html/rfc7364
- A Sajassi, et al., "BGP MPLS-Based Ethernet VPN," IETF RFC 7432, Feb 2015, https://tools.ietf.org/html/rfc7432

Student Questions

©2025 Raj Jain

Optional References

- A. Sajassi, et al, "Requirements for Ethernet VPN (EVPN)," IETF RFC 7209, May 2014, https://datatracker.ietf.org/doc/html/rfc7209
- J. Rabadan, et al, "Interconnection Solution for Ethernet VPN (EVPN) Overlay Networks," RFC 9014, 24 pp., May 2021
- S. Salam, et al, "Framework and Requirements for Ethernet VPN (EVPN) Operations, Administration, and Maintenance (OAM)," RFC 9062, 16 pp., June 2021
- A Sajassi, et al, "Integrated Routing and Bridging in Ethernet VPN (EVPN)," RFC 9135, 30 pp., October 2021
- J. Rabadan, et al, "IP Prefix Advertisement in Ethernet VPN (EVPN)," RFC 9136, 31 pp., October 2021
- J. Rabadan, et al, "Applicability of Ethernet Virtual Private Network (EVPN) to Network Virtualization over Layer 3 (NVO3) Networks," RFC 9469, 23 pp., September 2023
- A. Sajassi, et al, "Virtual Ethernet Segments for EVPN and Provider Backbone Bridge EVPN," RFC 9784, 20 pp., June 2025

Student Questions

©2025 Raj Jain

Optional References (Cont)

- X. Min, et al, "Bidirectional Forwarding Detection (BFD) for Generic Network Virtualization Encapsulation (Geneve)," RFC 9521, 11 pp., January 2024
- G. Mirsky, et al, "Active Operations, Administration, and Maintenance (OAM) for Use in Generic Network Virtualization Encapsulation (Geneve)," RFC 9772, 10 pp., May 2025.

Student Questions

©2025 Raj Jain

Wikipedia Links

- http://en.wikipedia.org/wiki/Generic_Routing_Encapsulation
- http://en.wikipedia.org/wiki/Locator/Identifier_Separation_Protocol
- http://en.wikipedia.org/wiki/Large_segment_offload
- http://en.wikipedia.org/wiki/Large_receive_offload
- https://en.wikipedia.org/wiki/Virtual_Extensible_LAN

Student Questions

©2025 Raj Jain

Acronyms

- ARMD Address Resolution for Massive numbers of hosts in the Data center
- ARP Address Resolution Protocol
- BGP Border Gateway Protocol
- BUM Broadcast, Unknown, Multicast
- CPU Central Processing Unit
- DC Data Center
- DCI Data Center Interconnection
- DCN Data Center Networks
- DCVPN Data Center Virtual Private Network
- DSCP Differentiated Services Control Point
- ECMP Equal Cost Multi Path
- EoMPLSoGRE Ethernet over MPLS over GRE
- ECN Explicit Congestion Notification
- EVPN Ethernet Virtual Private Network
- GRE Generic Routing Encapsulation

Student Questions

©2025 Raj Jain

Acronyms (Cont)

- IANA Internet Address and Naming Authority
- ID Identifier
- IEEE Institution of Electrical and Electronic Engineers
- IETF Internet Engineering Task Force
- IGMP Internet Group Multicast Protocol
- IP Internet Protocol
- IPSec IP Security
- IPv4 Internet Protocol V4
- IS-IS Intermediate System to Intermediate System
- LAN Local Area Network
- LISP Locator ID Separation Protocol
- LRO Large Receive Offload
- LSO Large Send Offload
- MAC Media Access Control
- MPLS Multi Protocol Label Switching
- MSS Maximum Segment Size

Student Questions

Acronyms (Cont)

- MTU Maximum Transmission Unit
- NIC Network Interface Card
- NV Network Virtualization
- NVA Network Virtualization Authority
- NVEs Network Virtualization Edge
- NVGRE Network Virtualization Using GRE
- NVO3 Network Virtualization over L3
- OAM Operation, Administration and Management
- OTV Overlay Transport Virtualization
- PB Provider Bridges
- PBB Provider Backbone Bridge
- pM Physical Machine
- pSwitch Physical Switch
- QoS Quality of Service
- RB Routing Bridge
- RFC Request for Comment

Student Questions

Acronyms (Cont)

RS	Routing System
STT	Stateless Transport Tunneling Protocol
TCP	Transmission Control Protocol
TLV	Type-Length-Value
TRILL	Transparent Routing over Lots of Links
TS	Tenant System
UDP	User Datagram Protocol
VDP	VSI Discovery and Configuration Protocol
VLAN	Virtual Local Area Network
VM	Virtual Machine
VN	Virtual Network
VNI	Virtual Network Instance/Virtual Network Context ID
VPLS	Virtual Private LAN Service
VPLSoGRE	Virtual Private LAN Service over GRE
VPN	Virtual Private Network

Student Questions

©2025 Raj Jain

Acronyms (Cont)

- VRRP Virtual Router Redundancy Protocol
- VSI Virtual Station Interface
- VSID Virtual Subnet Identifier
- vSwitch Virtual Switch
- VTEP VXLAN Tunnel End Point
- VXLAN Virtual Extensible Local Area Network

Student Questions

©2025 Raj Jain

Scan This to Download These Slides



Raj Jain
http://rajjain.com

http://www.cse.wustl.edu/~jain/cse5700-25/m_08dmt.htm

Student Questions

Related Modules



CSE567M: Computer Systems Analysis (Spring 2013),
https://www.youtube.com/playlist?list=PLjGG94etKypJEKjNAa1n_1X0bWWNyZcof

CSE473S: Introduction to Computer Networks (Fall 2011),



https://www.youtube.com/playlist?list=PLjGG94etKypJWOSPMh8Azcgy5e_10TiDw



Wireless and Mobile Networking (Spring 2016),
https://www.youtube.com/playlist?list=PLjGG94etKypKeb0nzyN9tSs_HCd5c4wXF

CSE571S: Network Security (Fall 2011),



https://www.youtube.com/playlist?list=PLjGG94etKypKvzfVtutHcPFJXumyyg93u



Video Podcasts of Prof. Raj Jain's Lectures,
https://www.youtube.com/user/ProfRajJain/playlists

Student Questions

©2025 Raj Jain